

Date

Customer




Project

Type

Drupl70 Suspended

With a name inspired by the effects of sunlight through droplets of water, this luminaire's high-quality light and anti-glare qualities are key to comfort and productivity in professional settings. Drupl is the perfect solution for office-compliant continuous lighting, around the working space as well as on the ceiling. Drupl combines the benefits of unique optical lenses and highly-performant LEDs with elegant design. Create a uniform light expression in your space with general light down and soft light up.





Base Profile

Dimensions	67mm x 70mm (h x w)
Base thickness	1.5mm
Mounting	Ceiling
Indoor/Outdoor	Indoor
Finish (RAL finish available on request)	Fine structured scratch resistant powder coating: white structure, black structure Brushed anodised: black matt
IP rating	IP20
Glow Wire Test	960°
CRI	90+
Warranty	5 years

Profile Cover

Finish	Fine structured scratch resistant powder coating: white structure, black structure Brushed anodised: gold, black matt
--------	---

Lenses

Type	PMMA
------	------

Lighting Modules

Linear Lighting

LED type	High power LED line
Colour temperature	2700K, 3000K, 4000K
Dimming	Non-dimmable, Dali/Pushdim Flicker-free (AM dimming)

Finish Information


(RAL finish available on request)



black structure
(powder coating)



black matt
(brushed anodised)




white structure
(powder coating)




gold
(brushed anodised)

Base Profile




- 93540032** DRUPL 70 BASE BLACK STRUC/M
- 93540083** DRUPL 70 BASE BLACK MATT/M
- 93540009** DRUPL 70 BASE WHITE STRUC/M




- 93540132** DRUPL 70 TOPCOVER BLACK STRUC/M
- 93540183** DRUPL 70 TOPCOVER BLACK MATT/M
- 93540109** DRUPL 70 TOPCOVER WHITE STRUC/M


Profile Cover



- 93540246*** DRUPL 70 CURVED COVER GOLD/M
- 93540232*** DRUPL 70 CURVED COVER BLACK STRUC/M
- 93540283*** DRUPL 70 CURVED COVER BLACK MATT/M
- 93540209*** DRUPL 70 CURVED COVER WHITE STRUC/M




- 93540346*** DRUPL 70 SHARP COVER GOLD/M
- 93540332*** DRUPL 70 SHARP COVER BLACK STRUC/M
- 93540383*** DRUPL 70 SHARP COVER BLACK MATT/M
- 93540309*** DRUPL 70 SHARP COVER WHITE STRUC/M




- 93540446*** DRUPL 70 STRAIGHT COVER GOLD/M
- 93540432*** DRUPL 70 STRAIGHT COVER BLACK STRUC/M
- 93540483*** DRUPL 70 STRAIGHT COVER BLACK MATT/M
- 93540409*** DRUPL 70 STRAIGHT COVER WHITE STRUC/M

Endplate




- 93543181** DRUPL 70 ENDPLATE LOW BLACK STRUC
- 93541183** DRUPL 70 ENDPLATE LOW BLACK MATT
- 93549181** DRUPL 70 ENDPLATE LOW WHITE STRUC



- 93543182** DRUPL 70 ENDPLATE HIGH BLACK STRUC
- 93543183** DRUPL 70 ENDPLATE HIGH BLACK STRUC
- 93549182** DRUPL 70 ENDPLATE HIGH WHITE STRUC


Connection




- 93540050** DRUPL 70 CONNECTION 180°

* Should be ordered for both sides


Fixation / Mounting



- 93540583** DRUPL 70 CONNECTION COVER FOR SUSP BLACK MATT
- 93540532** DRUPL 70 CONNECTION COVER FOR SUSP BLSTR
- 93540509** DRUPL 70 CONNECTION COVER FOR SUSP WHSTR




- 93540850** DRUPL 70 SUSPENSION BLACK STRUC
- 93540950** DRUPL 70 SUSPENSION WHITE STRUC




- 93001132** HINGE FOR HIGH CONE BLACK STRUC
- 93001109** HINGE FOR HIGH CONE WHITE STRUC


Electrical Supply




- 93540163** DRUPL70 HOLE FOR POWER SUPPLY 3-5P




- 93540164** DRUPL70 HOLE FOR POWER SUPPLY 6-9P




- 93003203** POWER FEED KIT 2M 3X1.5MM² BLACK STRUC
- 93002903** POWER FEED KIT 2M 3X1.5MM² WHITE STRUC
- 93003205** POWER FEED KIT 2M 5X1.5 BLACK STRUC
- 93002905** POWER FEED KIT 2M 5X1.5MM² WHITE STRUC
- 93003305** POWER FEED KIT 2M 6X0.75 BLACK STRUC
- 93003304** POWER FEED KIT 2M 6X0.75 WHITE STRUC




- 93003908** POWER FEED KIT 2M 9X0.75MM² BLACK STRUC
- 93003907** POWER FEED KIT 2M 9X0.75MM² WHITE STRUC




- 93003151** CONNECTION BOX 3P FOR TRANSPARANT CABLE BLACK STRUC
- 93002951** CONNECTION BOX 3P FOR TRANSPARANT CABLE WHITE STRUC
- 93003251** CONNECTION BOX 5P FOR TRANSPARANT CABLE BLACK STRUC
- 93003951** CONNECTION BOX 5P FOR TRANSPARANT CABLE WHITE STRUC
- 93003651** CONNECTION BOX 6P FOR TRANSPARENT CABLE BLACK STRUC
- 93003551** CONNECTION BOX 6P FOR TRANSPARENT CABLE WHITE STRUC



- 93005251** CONNECTION BOX 9P FOR TRANSPARENT CABLE BLACK STRUC
- 93005151** CONNECTION BOX 9P FOR TRANSPARENT CABLE WHITE STRUC



- 93002152** TRANSPARENT CABLE 3X1.5MM²/M
- 93002252** TRANSPARENT CABLE 5X1.5MM²/M
- 93003452** TRANSPARENT CABLE 6X0.75MM²/M
- 93003552** TRANSPARENT CABLE 9X0.75MM²/M



NON-DIM	-3-----
DALI/PUSHDIM	-8-----

Linear LED Fortimo LEDline DI

	2700K	3000K	4000K	Module length (mm)	Lens 80°	Lens 120°
2x	9X544502	9X544002	9X544102	560	93540016*	93540018*
3x	9X544503	9X544003	9X544103	840		
4x	9X544504	9X544004	9X544104	1120		
5x	9X544505	9X544005	9X544105	1400		
6x**	9X544506	9X544006	9X544106	1680		
7x**	9X544507	9X544007	9X544107	1960		

Lamp type	MED POWER LED
Delivered lumens**	3499lm/m (2700K) 3596lm/m (3000K) 3705lm/m (4000K)
Connected load**	24,8W/m (2700K, 3000K, 4000K)
Efficacy**	141lm/W (2700K) 145lm/W (3000K) 149lm/W (4000K)
UGR**	18
Binning	3SDCM
Lifetime	L80 B10 @50000hrs.

SUPPLEMENTS

93541000* PROFILE EMERGENCY PACK 3H


*only for 2700K, 3000K, 4000K in 6x and 7x

**values for lens 80°, white sharp cover, calculated via 5x LEDline

Technical values for straight cover white struc - 3000K

* Lens required: ordered quantity must be accoring to number of ledlines

** Emergency available for 6x en 7x



Linear LED Strip 24V Uplight

1000lm/m

	2700K	3000K	4000K
mounted/m	93000044	93000045	93000046

2000lm/m

	2700K	3000K	4000K
mounted/m	93000029	93000030	93000031

Lamp type	LED STRIP - diffuser included		
	1000lm/m	2000lm/m	
Delivered lumens	2700K	961lm/m	1507lm/m
	3000K	1137lm/m	1695lm/m
	4000K	1094lm/m	1702lm/m
Connected load	2700K	14.4W/m	14.4W/m
	3000K	14.4W/m	14.4W/m
	4000K	14.4W/m	14.4W/m
Efficacy	2700K	67lm/W	105lm/W
	3000K	79lm/W	118lm/W
	4000K	76lm/W	118lm/W
Binning	3SDCM		
Lifetime	L80 B10 @50000hrs.		

DRIVERS

93009520	LED DRIVER 24V 60W
93009552	LED DRIVER 24V 100W
96009520	LED DRIVER 24V 60W 1-10V
98009520	LED DRIVER 24V 100W DALI/PUSHDIM

SUPPLEMENTS

93541001	LED STRIP 24V CONNECTION
----------	--------------------------