

Date
Customer
Project
Type

Drupl70 Recessed

With a name inspired by the effects of sunlight through droplets of water, this luminaire's high-quality light and anti-glare qualities are key to comfort and productivity in professional settings. Drupl is the perfect solution for office-compliant continuous lighting, around the working space as well as on the ceiling. Drupl combines the benefits of unique optical lenses and highly-performant LEDs with elegant design. Create a uniform light expression in your space with general light down and soft light up.





DRUPL RECESSED CURVED COVER



DRUPL RECESSED CURVED COVER



DRUPL RECESSED STRAIGHT COVER



Base Profile

Dimensions	67mm x 70mm (h x w)
Mounting Depth	115mm
Base thickness	1.5mm
Mounting	Ceiling
Indoor/Outdoor	Indoor
Finish	Fine structured scratch resistant powder coating: white structure, black structure
IP rating	IP20
Glow Wire Test	960°
CRI	90+
Warranty	5 years

Profile Cover

Finish	Fine structured scratch resistant powder coating: white structure, black structure
--------	---

Lenses


Type	PMMA
------	------

Lighting Modules

Linear Lighting

LED type	High power LED line
Colour temperature	2700K, 3000K, 4000K
Dimming	Non-dimmable, Dali/Pushdim Flicker-free (AM dimming)

Finish Information




white structure
(powder coating)




black structure
(powder coating)

Base Profile




- 93570032** DRUPL 70 RECESSED BASE BLACK STRUC/M
- 93570009** DRUPL 70 RECESSED BASE WHITE STRUC/M

Connection




- 93570052** DRUPL 70 RECESSED CONNECTION 180° 3-5P
- 93570053** DRUPL 70 RECESSED CONNECTION 180° 6-9P

Profile Cover




- 93570232*** DRUPL 70 RECESSED CURVED COVER BLACK STRUC/M
- 93570209*** DRUPL 70 RECESSED CURVED COVER WHITE STRUC/M

Fixation / Mounting




- 93570996** DRUPL 70 RECESSED BRACKET




- 93570432*** DRUPL 70 RECESSED STRAIGHT COVER BLACK STRUC/M
- 93570409*** DRUPL 70 RECESSED STRAIGHT COVER WHITE STRUC/M

Electrical Supply



- 93570050** DRUPL 70 RECESSED HOLE FOR POWER SUPPLY 3-5P
- 93570051** DRUPL 70 RECESSED HOLE FOR POWER SUPPLY 6-9P

Endplate




- 93573181** DRUPL 70 RECESSED ENDPLATE LOW BLACK STRUC
- 93579181** DRUPL 70 RECESSED ENDPLATE LOW WHITE STRUC

Supplement

- 93570215** DRUPL 70 RECESSED RAL SUPPL. CURVED COVER/M
- 93570188** DRUPL 70 RECESSED RAL SUPPL. ENDPLATE
- 93570415** DRUPL 70 RECESSED RAL SUPPL. STRAIGHT COVER/M
- 93570010** DRUPL 70 RECESSED RAL SUPPL. BASE/M
- 93000101** DRUPL 70 RECESSED RAL SET UP CHARGE

* Should be ordered for both sides



NON-DIM	-3-----
DALI/PUSHDIM	-8-----

Linear LED Fortimo LEDline DI

Lamp type	MED POWER LED
Delivered lumens**	3499lm/m (2700K) 3596lm/m (3000K) 3705lm/m (4000K)
Connected load**	24,8W/m (2700K, 3000K, 4000K)
Efficacy**	141lm/W (2700K) 145lm/W (3000K) 149lm/W (4000K)
UGR**	18
Binning	3SDCM
Lifetime	L80 B10 @50000hrs.

SUPPLEMENTS

93541000* PROFILE EMERGENCY PACK 3H

*only for 2700K, 3000K, 4000K in 6x and 7x

**values for lens 80°, white sharp cover, calculated via 5x LEDline

	2700K			Module length (mm)
	LENS 50°	LENS 80°	LENS 120°	
2x	9X571202	9X572202	9X575202	560
3x	9X571203	9X572203	9X575203	840
4x	9X571204	9X572204	9X575204	1120
5x	9X571205	9X572205	9X575205	1400
6x	9X571206	9X572206	9X575206	1680
7x	9X571207	9X572207	9X575207	1960

	3000K			Module length (mm)
	LENS 50°	LENS 80°	LENS 120°	
2x	9X571302	9X572302	9X575302	560
3x	9X571303	9X572303	9X575303	840
4x	9X571304	9X572304	9X575304	1120
5x	9X571305	9X572305	9X575305	1400
6x	9X571306	9X572306	9X575306	1680
7x	9X571307	9X572307	9X575307	1960

	4000K			Module length (mm)
	LENS 50°	LENS 80°	LENS 120°	
2x	9X571402	9X572402	9X575402	560
3x	9X571403	9X572403	9X575403	840
4x	9X571404	9X572404	9X575404	1120
5x	9X571405	9X572405	9X575405	1400
6x	9X571406	9X572406	9X575406	1680
7x	9X571407	9X572407	9X575407	1960