

# Recessed ring Ø82 2x

13241130

**INSTALLATION IN DRYWALL**

1.1

Ø111

90 mm

1.2

ADJUST HEIGHT

click

click

SCREWS ARE NOT INCLUDED

1.3

REINFORCE PLASTERFINISH WITH FIBREGLASS JOINT COVER TO AVOID CRACKS

**INSTALLATION IN CONCRETE WITH PLASTER FINISH**

1.1

90 mm

250 mm

Ø111

ADJUST HEIGHT

click

click

1.2

REINFORCE PLASTERFINISH WITH FIBREGLASS JOINT COVER TO AVOID CRACKS

2

MODUPOINT DEEP REC ACCESSORY SHOULD BE ORDERED SEPARATELY

3

**DRIVER POSITION FOR SERIAL CONTROL**

Min 20 mm

**DRIVER POSITION FOR SEPARATE CONTROL**

Min 20 mm

**DRYWALL**

106 mm

262 mm

300 x 170 mm

Min 150 mm

Min 10,5 mm

Max 35 mm

**CONCRETE WITH PLASTER FINISH**

Min 110 mm

Min 11,5 mm

Max 35 mm

**CONCRETE WITH PLASTER FINISH**

FOR THIN PLASTER, MOUNT PLASTER FRAME AT FRONT

Min 110 mm

Min 4,5 mm

Max 35 mm