

Recessed ring Ø82

13241030

INSTALLATION IN DRYWALL

1.1

Ø111

driver -

driver +

1.2

ADJUST HEIGHT

SCREWS ARE NOT INCLUDED

1.3

REINFORCE PLASTERFINISH WITH FIBREGLASS JOINT COVER TO AVOID CRACKS

INSTALLATION IN CONCRETE WITH PLASTER FINISH

1.1

Ø111

75mm

140mm

driver -

driver +

1.2

ADJUST HEIGHT

REINFORCE PLASTERFINISH WITH FIBREGLASS JOINT COVER TO AVOID CRACKS

2

driver -

driver +

click

MODUPOINT DEEP REC ACCESSORY SHOULD BE ORDERED SEPERATELY

3

DRYWALL

235 x 160 mm

Min 120 mm

70 mm

Min 10,5 mm

Max 30 mm

Modular LED-driver

Min 20 mm

CONCRETE WITH PLASTER FINISH

Ø111 mm

Min 110 mm

Min 11,5 mm

Max 30 mm

CONCRETE WITH PLASTER FINISH

Ø111 mm

Min 110 mm

Min 4,5 mm

Max 30 mm

FOR THIN PLASTER, MOUNT PLASTER FRAME AT THE FRONT