

Chival Wall UP/Down 2x LED 1800-3000K WD Medium DE

137608XX

1

✓

ONLY VERTICAL WALL MOUNTING

✗

SCREWS NOT INCLUDED

max Ø4,5 mm

max Ø8,5 mm

+

RED

+

LED

11mm

0,2 - 4mm²

24 - 12 AWG

42 mm

39 mm

84 mm

17,5 mm

Ø15 mm

2

1

LED

+

LED

2

OFF

WARM DIM

ELECTRICAL SPECS LED-FIXTURE

Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
250	31	37	8

+

 RED

-

 BLACK

For serial connection, respect polarity!  
Not suited for connection to mains voltage.  
Combine with a Modular LED-driver.

3

1.5

6,5 mm

USE A SLIM SCREW DRIVER TO PREVENT DAMAGE TO THE WALL

4

⚡

ESD

PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

⚡

LIGHT SOURCE - DO NOT TOUCH LED

Touching the LED can result in permanent damage of the light source. The light source and/or driver contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

03 - 02/07/2025

III

↔

➡

IP 20

✓

UK CA

CE