Modest 74 Leaf Spring IP55 LED DE

137800XX_137801XX_137804XX_137805XX

1



ELECTRICAL SPECS LED FIXTURE			
Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	13,2	15,0	5,0
500	13,7	15,4	7,2
RED		BLACK	
For serial connection, respect polarity! Not suited for connection to mains voltage. Combine with a Modular LED-driver.			

Minimum volume requirement

In false ceiling – with driver:



* check the tilt-in height for drivers

In concrete slab:



** For solid wood or CLT the installation hight should be > 140mm

2



IP20	wago connectors included
IP55	waterproof connectors not included Modular reference number : 1000385

3







Replace protective shield when broken. The luminaire shall only be used complete with its protective shield.
Reference number: 1014946

LIGHT SOURCE - DO NOT TOUCH LED

Touching the LED can result in permanent damage of the light source.The light source and/or driver contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

DRIVERS & ACCESSORIES

For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.