

SLD50 recessed bracket trimless

93590056

Cut-out size

(Length + 5mm) x 56mm

LENGTH
PROFILE LENGTH + 5mm

WIDTH
MINIMUM 54mm
MAXIMUM 56mm

MINIMUM 8mm
MAXIMUM 25mm

PROFILE LENGTH

see profile drawing for distance

SCREWS NOT INCLUDED

4

Use FLEX filler

OFF

Use FLEX filler

Use FLEX filler

Dimensions.

147 mm
137 mm

min. 6mm
max. 30mm

110mm
115mm

min. 2mm
max. 3mm

50

min. 2mm
max. 3mm

Use FLEX filler

Use FLEX filler

Replace protective shield when broken. The luminaire shall only be used complete with its protective shield.
On site conditions (e.g. heat, humidity, ...) can lead to expansion of the diffuser. Therefore onsite shortening of the diffuser can be required.

LIGHT SOURCE - DO NOT TOUCH LED

Touching the LED can result in permanent damage of the light source. The light source and/or driver contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

DRIVERS & ACCESSORIES

For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.