




Nyto Semi-Recessed Adjustable 30 1x LED SPOT


138240XX_138243XX

1.1 INSTALLATION




ELECTRICAL SPECS LED-FIXTURE			
Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	11,4	12,2	4,1
 RED		 BLACK	
For serial connection, respect polarity! Not suited for connection to mains voltage. Combine with a Modular LED-driver.			


1.2 INSTALLATION




1.3 INSTALLATION





2.1 UNINSTALL



2.2 UNINSTALL



Minimum volume requirement



Replace protective shield when broken. The luminaire shall only be used complete with its protective shield.
Reference number: 1016387

LIGHT SOURCE - DO NOT TOUCH LED
Touching the LED can result in permanent damage of the light source. The light source and/or driver contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

PREVENTING ELECTROSTATIC DAMAGE
A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

DRIVERS & ACCESSORIES
For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.