

# Smart Tube Surface 48 Outdoor 1x DE

139300XX

**1**

7mm  
MAX 0.95mm<sup>2</sup>  
MAX 18AWG

Ø4.8  
32  
Ø52

**2**

IP54 only when used with included silicone ring and in closed ceiling

SCREWS NOT INCLUDED  
max Ø4,5 mm  
max Ø8,5 mm

**3**

driver + - driver

MUST BE USED WITH:  
- Smart Lolis Rec 48 Outd 1x HO IP55 LED

INSTALL UNINSTALL

**4**

NOT SUITABLE FOR INSTALLATION  
≤5KM FROM THE COAST

**CLEANING INSTRUCTIONS**

To avoid corrosion, clean at least quarterly with a non-abrasive cloth and a neutral detergent. Parts of the fixture which are not protected by the installation housing may not come into contact with the ground or aggressive chemical material (e.g. fertilizers, weed killers, lime,...). Excessive use of de-icing agent in the vicinity of the fixture must be avoided.

**PREVENTING ELECTROSTATIC DAMAGE**

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

**DRIVERS & ACCESSORIES**

For latest version of driver matrix and available accessories check [www.supermodular.com](http://www.supermodular.com) or connect with your sales contact.

