

SLD20 Surface

Light in form, pure in function. With its slim 20 mm profile, SLD20 brings elegant light lines to any space. Customisable in length, colour, and configuration, it ensures seamless applications and a stylish ambience.



SLD20 SURFACE - BRONZE BRUSHED ANODISED



SLD20 SURFACE - WHITE STRUCTURE



SLD20 SURFACE - BLACK STRUCTURE

Base Profile

Dimensions	20mm x 35mm (h x w)
Base thickness	1,5mm
Mounting	Ceiling
Indoor/Outdoor	Indoor
Finish (RAL finish available on request)	Brushed anodised: bronze, champagne, silver bronze Fine structured scratch resistant powder coating: black, white
IP rating	IP20
Glow Wire Test	960°
CRI	90+
Warranty	5 years


Diffuser

Type	Polycarbonate (poly and poly in)

Lighting Modules

Linear Lighting module

LED type	LED strip 24V IP20 / IP65
Colour temperature	2700K, 3000K, 4000K (3500K on request)
Dimming	Non-dimmable, 1-10V, 0-10V, Dali/Pushdim



Finish Information

(RAL finish available on request)




silver bronze
(brushed anodised)



bronze
(brushed anodised)



champagne
(brushed anodised)




white structure
(powder coating)




black structure
(powder coating)

Base Profile




- 93630009** SLD20 PROFILE SURFACE WHITE STRUCTURE /M
- 93630032** SLD20 PROFILE SURFACE BLACK STRUCTURE /M
- 93630082** SLD20 PROFILE SURFACE BRONZE BRUSHED ANODISED /M
- 93630041** SLD20 PROFILE SURFACE CHAMPAGNE BRUSHED ANODISED /M
- 93630084** SLD20 PROFILE SURFACE SILVER BRONZE BRUSHED ANODISED /M

Diffuser




- 93632100** SLD20 DIFFUSER IN /M




- 93632000** SLD20 DIFFUSER /M

Endplate




- 93631009** SLD20 ENDPLATE WHITE STRUCTURE
- 93631032** SLD20 ENDPLATE BLACK STRUCTURE
- 93631015** SLD20 ENDPLATE CHAMPAGNE BRUSHED
- 93631014** SLD20 ENDPLATE BRONZE BRUSHED
- 93631016** SLD20 ENDPLATE SILVER BRONZE BRUSHED

Fixation / Mounting




- 93632800** SLD20 SPRING FOR FIXATION


Connection




- 93632500** SLD20 CONNECTION 90° MECHANICAL



- 93632400** SLD20 CONNECTION 180° MECHANICAL



- 93633000** SLD20 CONNECTION LEDSTRIP 24V (FOR RECESSED AND SURFACE MOUNTING)



Linear LED Strip 24V

1000lm/m


	2700K	3000K	4000K
mounted/m	93000540	93000541	93000542

2000lm/m

	2700K	3000K	4000K
mounted/m	93000004	93000005	93000006

Lamp type	LED STRIP - diffuser poly included		
Delivered lumens		1000lm/m	2000lm/m
	2700K	794lm/m	1390lm/m
	3000K	847lm/m	1420lm/m
	4000K	770lm/m	1352lm/m
Connected load	2700K	10.8W/m	18.9W/m
	3000K	10.8W/m	18.9W/m
	4000K	9.6W/m	16.6W/m
Efficacy	2700K	74lm/W	74lm/W
	3000K	78lm/w	75lm/W
	4000K	80lm/W	81lm/W
Binning	3SDCM		
Lifetime	L80 B10 @50000hrs		

DRIVERS	
12405830	LED DRIVER 24V 20W
12405030	LED DRIVER 24V 150W
12402030	LED DRIVER 24V 20W 1-10V
12409730	LED DRIVER 24V 60W NON-DIM/0/1-10V
12409830	LED DRIVER 24V 100W NON-DIM/0/1-10V
12409930	LED DRIVER 24V 150W NON-DIM/0/1-10V
13550830	LED DRIVER 24V 100W PUSHDIM/DALI
13550930	LED DRIVER 24V 150W PUSHDIM/DALI



Linear LED Strip 24V IP65

1000lm/m

	2700K	3000K	4000K
mounted/m	93000013	93000014	93000015
not mounted (roll 5m)	93000016	93000017	93000018

2000lm/m

	2700K	3000K	4000K
mounted/m	93000047	93000048	93000049
not mounted (roll 5m)	93000026	93000027	93000028

Lamp type	LED STRIP - diffuser poly included		
		1000lm/m	2000lm/m
Delivered lumens	2700K	691lm/m	1208lm/m
	3000K	734lm/m	1285lm/m
	4000K	894lm/m	1417lm/m
Connected load	2700K	9.6W/m	16.8W/m
	3000K	9.6W/m	16.8W/m
	4000K	9.6W/m	16.8W/m
Efficacy	2700K	72lm/W	72lm/W
	3000K	77lm/w	77lm/w
	4000K	93lm/W	84lm/W
Binning	3SDCM		
Lifetime	L80 B10 @50000hrs.		

DRIVERS

12405830	LED DRIVER 24V 20W
13551130	LED DRIVER 24V 60W
13551230	LED DRIVER 24V 100W
13551330	LED DRIVER 24V 150W
12402030	LED DRIVER 24V 20W 1-10V
12409730	LED DRIVER 24V 60W 1-10V
12409830	LED DRIVER 24V 100W 1-10V
12409930	LED DRIVER 24V 150W 1-10V
12405030	LED DRIVER 24V 150W
13550930	LED DRIVER 24V 150W PUSHDIM/DALI
13550830	LED DRIVER 24V 100W PUSHDIM/DALI