

Minude Surface Adjustable 45 2x LED Med DE

139421XX_139431XX

1

**! MOUNT LED DRIVER
REMOTE AND ACCESSIBLE**

driver - + driver

SCREWS NOT INCLUDED

max Ø4,5 mm max Ø8,5 mm

35 mm 12 mm 50 mm 150 mm

2

driver - + driver

BLACK - + RED

3

click

ELECTRICAL SPECS FIXTURE			
Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	29,6	36	11,4
500	30,4	37,2	17
+ RED - BLACK			
For serial connection, respect polarity! Not suited for connection to mains voltage. Combine with a Modular LED-driver.			

ELECTRICAL SPECS LED			
Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	14,8	18	5,7
500	15,2	18,6	8,5
+ RED - BLACK			
For serial connection, respect polarity! Not suited for connection to mains voltage. Combine with a Modular LED-driver.			

! SERIAL CONNECTION 1 DRIVER

Always use a serial connection for multiple luminaires on a single driver!
Only use luminaires with the same input ratings!

! 1 LED 1 DRIVER

Always use a serial connection for multiple luminaires on a single driver!
Only use luminaires with the same input ratings!

DRIVERS & ACCESSORIES

For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.

4

5 UNINSTALL