




Nyto Surface Adjustable 30 Round 1x LED DE

139901XX_139902XX_139904XX_139905XX

1




ELECTRICAL SPECS LED-FIXTURE


Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	15,4	18,8	6
+ RED		- BLACK	

For serial connection, respect polarity!
Not suited for connection to mains voltage.
Combine with a Modular LED-driver.

CUT-OUT HOLES




2




ONLY TO BE INSTALLED OUTSIDE ARM'S REACH

3





SERIAL CONNECTION:



Always use a serial connection for multiple luminaires on a single driver!
Only use luminaires with the same input ratings!

4



LIGHT SOURCE - DO NOT TOUCH LED

Touching the LED can result in permanent damage of the light source. The light source and/or driver contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.



PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

SERVICEABLE COMPONENTS & ACCESSORIES

For latest version of available accessories or serviceable components check www.supermodular.com or connect with your sales contact.