



Smart Cake/Kup/Lotis 82 IP LED DE

124120XX 124121XX 124122XX 124123XX 124123XX 124125XX 124125XX 124125XX 124125XX 124125XX 124126XX 124225XX 12422XX 1242XX 1242X












ELECTRICAL SPECS LED-FIXTURE			
Drive Current (mA)	Forward Voltage		Power
	min (Vf)	max (Vf)	(W)
350	16,5	19,2	6,2
500	17,1	19,8	9,2
O RED		■ BLACK	

For serial connection, respect polarity! Not suited for connection to mains voltage. Combine with a Modular LED-driver.









3



Replace protective shield when broken. The luminaire shall only be used complete with its protective shield. Reference number: 1010754



LIGHT SOURCE - DO NOT TOUCH LED

Touching the LED can result in permanent damage of the light source. The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.





PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.



For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.





SERIAL CONNECTION:

















