

Mini multiple trimless for smartrings 3x LED



125370XX-B1_125371XX-B1_125372XX-B1

1

Has to be combined with :
10460730 Mini-multiple trimless 3L recessed frame

312x107mm

hole dimension without recessed frame.

| ELECTRICAL SPECS LED-FIXTURE | | | |
|---|-----------------|---|--------------|
| Drive Current (mA) | Forward Voltage | | Power (W) |
| | min (Vf) | max (Vf) | |
| 350 | 13,2 | 15,0 | 5,0 |
| 500 | 13,7 | 15,4 | 7,2 |
|  RED | |  BLACK | |
| For serial connection, respect polarity! Not suited for connection to mains voltage. Combine with a Modular LED-driver. | | | |

250 x 350 mm

120 mm

115 mm

Min. 1mm
max. 25mm

2

3

Frontrings Smart flatring:

Turn

Frontrings Smart kup-Cake-Lotis ring:

Push

4

LIGHT SOURCE - DO NOT TOUCH LED
Touching the LED can result in permanent damage of the light source. The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

PREVENTING ELECTROSTATIC DAMAGE
A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

DRIVERS & ACCESSORIES
For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.