

Extruded suspension kit 2m surface Tre dim GI

135232XX_135236XX

1 CONNECT SUSP KIT WITH LED-MODULE

1.1

EXTRUDED GEAR INCLUDED
SUSP KIT INCLUDED

1.2

LED-MODULE NEEDS
TO BE ORDERED
SEPERATELY.

1.3

2x T10

WEIGHT OF LIGHTING
FIXTURE SHOULD ALWAYS
BE CARRIED BY THE
STEELCABLE !

1.4

1.6

1.5

2x T10

LED-MODULE NEEDS
TO BE ORDERED
SEPERATELY.

2

Ø170 mm

Ø144 mm

11mm

0.2 - 4mm²
24 - 12 AWG

≤ Ø4 mm

≤ Ø8 mm

3.1 LOOSEN THE SCREW

2x T10

3.4 LOOSEN THE SCREWS

2x T10

3.2 ADJUST STEELCABLE LENGTH

PUSH WHILE ADJUSTING CABLE

3.5 ADJUST POWERCABLE LENGTH

3.3 TIGHTEN THE SCREW

2x T10

3.6 TIGHTEN THE SCREWS

2x T10

4

click

WEIGHT OF LIGHTING
FIXTURE SHOULD ALWAYS
BE CARRIED BY THE
STEELCABLE !

Replace protective shield when broken. The luminaire shall only be used complete with its protective shield.
Reference number: 1014810

PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Always be properly grounded when touching leads or circuitry inside the luminaire. Use a wrist strap connected by a ground cord to the housing. Avoid touching the light sources with bare hands.

DRIVERS & ACCESSORIES

For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.

01 - 09/09/2020

R,C ↑ IP 20 CE