

Kompas Ceiling Base Ø340 350mA / 500mA 60W TRE


135700XX_135703XX

Scan for installation video or go to
supermodular.com/en/kompas-round-surface/





1 REMOVE COVER AND MOUNT ON CEILING




220-230V
50-60Hz
N ⊕ L



SCREWS NOT INCLUDED
max Ø5,5 mm
max Ø9,5 mm



2 CONNECT PRIMARY WIRES



PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.


Kompas Ceiling Base Ø340 350mA / 500mA 60W TRE

135700XX_135703XX


3 CHECK MAX FIXTURES TOTAL \ DRIVER

	Fixture for Kompas	Extra	350mA		500mA	
			Includes 6 drivers Specs per driver: 10W 12 - 28 Vf 350mA		Includes 6 drivers Specs per driver: 10W 10 - 20 Vf 500mA	
			Max Fixtures Total	Max Fixtures Per LED Output In Series	Max Fixtures Total	Max Fixtures Per LED Output In Series
MONOCOLOR	Extruded GE		6	1	6	1
	Marbul Susp Fix		6	1	6	1
	Marbul Susp Adj		6	1	6	1
	Minude		6	1	6	1
	Placebo Down	+ optional shade	6	1	not compatible use 350mA version	
	Placebo Up		6	1		
	Smart Ball 82	+ Smart 82 + Smart 82 Adjustable	6	1	6	1
	Smart Ball 115	+ Smart 115 + Smart 115 Adj	- 6	- 1	- 6	- 1
	Smart Tubed Suspension 48 GE	+ Smart 48 + Smart 48+	use 30W version 12 min 2 / max 2		use 30W version 12 min 2 / max 2	
	Smart Tubed Suspension 82 L / XL GE	+ Smart 82 + Smart 82 Adj	6	1	6	1
	Smart Tubed Suspension 115 GE	+ Smart 115 + Smart 115 Adj	- 6	- 1	- 6	- 1
WARM DIM	Extruded WD GE		6	1	not compatible use 350mA version	
	Marbul Susp Fix Warm Dim		-	-		
	Marbul Susp Adj Warm Dim		-	-		
	Placebo Down Warm Dim	+ optional shade	6	1		
	Placebo Up Warm Dim		6	1		
	Smart Ball 82	+ Smart 82 Warm Dim + Smart 82 Adj Warm Dim	6	1		
	Smart Ball 115	+ Smart 115 Adj Warm Dim	-	-		
	Smart Tubed Suspension 48 GE	+ Smart 48 Warm Dim	-	-		
	Smart Tubed Suspension 82 L / XL GE	+ Smart 82 Warm Dim + Smart 82 Adj Warm Dim	6	1		
	Smart Tubed Suspension 115 GE	+ Smart 115 Adj Warm Dim	-	-		


4 CONNECT FIXTURES FOR KOMPAS




4.A LOOSEN STRAIN RELIEF



4.B GUIDE CABLE




4.C FIX STRAIN RELIEF




Kompas Ceiling Base Ø340 350mA / 500mA 60W TRE

135700XX_135703XX

5 CONNECT SECONDARY WIRES



6 CLOSE COVER



7 FINISHED

