

# Recessed ring Ø50

13642030

**INSTALLATION IN DRYWALL**

**1.1**

driver -      + driver

**1.2**

ADJUST HEIGHT

+

SCREWS ARE NOT INCLUDED

**INSTALLATION IN CONCRETE WITH PLASTER FINISH**

**1.1**

65 mm      125 mm

driver -      + driver

ADJUST HEIGHT

**2**

driver -      + driver

click

MINUDE RECESSED TRIMLESS 49 SHOULD BE ORDERED SEPERATELY

**1.3**

REINFORCE PLASTERFINISH WITH FIBREGLASS JOINT COVER TO AVOID CRACKS

**1.2**

REINFORCE PLASTERFINISH WITH FIBREGLASS JOINT COVER TO AVOID CRACKS

**3**

**DRYWALL DI**

Modular LED-driver

Min 200 x 200 mm

Min 100 mm

Min 20 mm      Min 10,5 mm      Max 30 mm

**CONCRETE WITH PLASTER FINISH DE**

Ø79 mm

Min 100 mm

Min 11,5 mm      Max 30 mm

**CONCRETE WITH PLASTER FINISH DE**

FOR THIN PLASTER, MOUNT PLASTER FRAME AT THE FRONT

Ø79 mm

Min 100 mm

Min 4,5 mm      Max 22 mm